



Laminating and
Finishing **SYSTEMS**

EXCELAM 1100 SWING

Large Format Graphic
Roll Laminator



 **skandacor**™ The proactive finish.™

1.888.820.9020
skandacor.com

EXCELAM 1100 SWING

Excelam-Swing Series has a built-in “Multi-Step” pressure control device to control the roller pressure for all kinds of paper. This machine is the best laminator for photocopy centers and graphic printing shops. Available in both 43”(1100mm) and 65”(1670mm) widths.

Finishing Applications in Wide Format Print Shops



Max. 43"



3 m/min



220-240 V, 20 A.

Specifications

| | EXCELAM 1100 SWING |
|-------------------------|-------------------------------------|
| Laminating Speed | 3 m/min |
| Laminating Width | 43" |
| Film Thickness | Up to 10 mil |
| Substrate weight | 80 gsm~350 gsm |
| Max. Mounting Thickness | 0.5" |
| Front Roller Diameter | 3.1" |
| Rear Roller Diameter | 2.36" |
| Warm Up Time | 22 min |
| Heating System | Hot Roller Internal Infrared Heater |
| Dimensions | 59" x 27.9" x 49.2" |
| Electrical | 220-240 V, 20 A |

Skandacor™ equipment works brilliantly with our lineup of **TRADEpro™** Wide Format UV Low-Melt and Cold laminate films.



TRADE
Laminate Films

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.