



Laminating and
Finishing **SYSTEMS**

RSL 2702

27" Desktop
Hot and Cold Roll Laminator/Mounter



RSL 2702

Designed as a scaled-down model of the commercial laminators, the **RSL 2702** 27" Hot Roll Laminator/Mounter offers speed, versatility, and convenience. It is capable of laminating both thermal and pressure sensitive films up to 27" wide at speeds up to 8.2' per minute. The adjustable roller gap allows for encapsulating prints with maximum pressure, or gapping the rollers to do mounting on substrates up to 3/16" thick. The release liner take up facilitates material take up such as the release liner on PSpro laminates, or the excess foil when sleeeking. It includes many features such as auto-off and stand-by modes, document guides, a rear cross cutter, digital speed and temperature controls, multiple set-up memory channels, and pull out film shafts and drop down idler. Compact in size but a work horse in every respect.

Finishing Applications in On-Demand Copy and Print Shops, Educational, and Office Settings

Specifications



Max. 27" wide



Up to 8.2 ft/min.
Variable
Speed Settings



110 V

	RSL 2702
Laminate	2.25" and 3" Core Mandrels (1" Core Optional) / Accepts All Laminate Finishes / All Roll Widths up to 27" (max. 7.9' Roll Diameter)
Film Thickness	up to 10.0 mil
Material Thickness	Up to 3/16"
Speed	up to 8.2 ft/min (with 9 Variable Speed Settings)
Warm Up	Approximately 10 min
Temperature	Independent Upper and Lower Variable Temperature Control (302°F max.) / Heated Rollers
Cutting	Built-in Rear Cross Cutter
Functions	Auto Shut-Off and Standby Functions / Reverse Switch / Safety Shield with Lockout Switch / Document Guides / Cooling Fans
Dimensions	38" L x 21.5" W x 18.5" H
Weight	124 lbs
Electrical	110 V, 60Hz
Warranty	1 Year on Parts, 6 Months on Rollers

Skandacor™ equipment works brilliantly with our lineup of pro™ Trade and Specialty laminate films.



TRADE
Laminate Films



SPECIALTY
Thermal
Laminate Films

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.