



Laminating and
Finishing **SYSTEMS**

DIGITAL 44

Dual Hot Roll Laminator




DIGITAL 44


The **Digital 44** laminator can do all the finishing tasks required of a large format imaging shop - laminating one or two sided, encapsulating, mounting with heat activated (dry mount) or cold pressure sensitive adhesives, simultaneously mount and laminate and application of cold adhesives. The Digital 44 laminator was made to be very easy to use. Standard features include variable speed, independent top and bottom heat control, spacious feed tray and a powerful film cooling system.

Finishing Applications in On-Demand Print Shops, Educational, and Office Settings.


Specifications



Max. 44" wide



0-30 FPM
Variable
Speed Settings



208-240V 30 amps
(Single-Phase)

DIGITAL 44	
Maximum Laminating Width	44"
Variable Speed	0-30 FPM
Laminating Roller Diameter	3 1/8"
Supply Roll Core Size	3"
Recommend Film Thickness	Up to 10 mil
Maximum Laminating Thickness	1/2"
Maximum Diameter Roll of Film	12"
Dimensions	62"L x 60"H x 34"W
Shipping Dimensions	71"L x 43"W x 62"H
Weight / Shipping Weight	550 lba. / 850 lbs.
Motor	1/4 HP D/C
Electrical	208-240V 30 amps (Single-Phase)
Warranty	Two-year factory warranty

Skandacor™ equipment works brilliantly with our lineup of **pro™** Trade and Specialty laminate films.



TRADE
Laminate Films



SPECIALTY
Thermal
Laminate Films

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.