



Laminating and  
Finishing **SYSTEMS**

# PT 33LSC

Fully Automated Laminator



# PT 33LSC

The **PT 33LSC** is the world's first fully automated laminator that slits and cuts to finished size, saving hours of trimming and cutting after the laminating process. Designed to meet the demands of the digital short run printer, the **PT 33LSC** not only cuts to bleed but has pouch mode where you can choose your encapsulation size or perform true single sided laminating with the ability to easily control the curl with the anti-curl device. Automatic setup, productive speeds and the efficient pile feeder makes for a 'set it and forget it' laminating experience.

**Finishing Applications** in On-Demand Print Shops, Educational, and Office Settings.



Max. 13" x 19.7"



10 feet  
per minute



110 V

## Specifications

	PT 33LSC
Minimum Sheet Size	7" x 7" (17.78 cm x 17.78 cm)
Maximum Sheet Size	13" x 19.7" (33.02 cm x 50.038 cm)
Speed	Variable speeds up to 10 feet per minute
Paper Thickness	100-350 gsm
Lamination Thickness	1.5, 3 & 5 mil
Lamination Width	4.4" – 12.9" (11.176 cm – 32.766 cm)* custom widths available
Laminating Modes	Double-sided, single-sided with anti-curl device with no need for release film, adjustable encapsulation and trim to bleed
Cutting Method	2 automatic setup side slitters and 1 guillotine cutter assembly
Feeding Method	2" (5.08 cm) vacuum pile feeder
Electrical	110-130v, 50/60hZ, 15a



**Skandacor™** equipment works brilliantly with our lineup of pro™ Trade and Specialty laminate films.



**TRADE**  
Laminate Films



**SPECIALTY**  
Thermal  
Laminate Films

**Note:** The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.